2015.07.14 - Helium Polish version 5.6.76.1, report.dll version 2.6.10.1, dx.dll version 5.8.0.0, PacorHWS.dll version 4.0.33.0, OHWS_Reflect2.dll version 1.5.54.517, new templates dd 13.07.2015

Release contains:


File	Version			
HeliimPolish.exe	5.6.76.1			
report.dll	2.6.11.1			
dx.dll	5.8.0.0			
PacorHWS.dll	4.0.33.0			
OHWS_Reflect2.dll	1.5.54.517			
Reports templates	2015-07-13			

In this version we made following changes:

- 1. Support of new CUB HP_SMC for HPP software. So you will be able to make calibration and alignment of HPReflect scanner (shadow stage) initially with HP_SMC board not changing HP old CUB to HP_SMC. Please note that it is necessary to place OHWS_Reflect2.dll version 1.5.54.517 or later in root folder of HPP to work with HP_SMC board.
- 2. Criteria to differentiate a Cushion from Oval is changed. New rule allow to separates cut more precisely.
- 3. Criteria to differentiate a StepCut from Radiant is changed. Before problem was that models was built by AnyCut algorithm and determined as Radiant but not StepCut. Since this version models determined as StepCut.
- 4. Calculation of Table for Oval, Marquise, Pear and Cushion is changed please refer to bookmarks: TABLE_MM_X, TABLE_PC_X, WIDTH_TABLE_MM, WIDTH_TABLE_PC, LENGTH_TABLE_MM, LENGTH_TABLE_PC.

Tubic	70	00.44		02.10	1		l	1	1
Table	mm	4.739		6.990					
Table by width & length									
Width		1	8.396 mm, 1	00%	Length			11.242 mm,	100%
Table by width		4	739 mm 56	44 %	Table by len	ath		6 990 mm 6	2 18 %

5. Illustrated HTML report for Cushion, AnyCut, Princess as it was few months ago for RBC:



- 6. Changes in algorithm of facets determination of RBC. This allows to fix many problem samples with wrong determination.
- 7. In this version we fixed issue with table parameters calculation for semi polish RBC:

Table	%	59.37	59.12	59.72	0.61
Table	mm	2.594	2.583	2.609	0.027
Table inside	%	59.37	59.12	59.72	0.61
Table inside	mm	2.594	2.583	2.609	0.027
Table outside	%	63.97	63.90	64.18	0.28
Table outside	mm	2.795	2.791	2.804	0.012
Table obsolete	%	59.39	59.12	59.74	0.62
Table obsolete	mm	2.594	2.583	2.610	0.027
t 					